

CF1400E 12000BTU



- Sleek Design
- Electronic panel display
- 24-hour timer
- Remote control
- Unique evaporation booster for high efficient cooling
- 3-speed turbo fan with sleep mode
- R410A green refrigerant for improved cooling
- Cable management compartment at the back
- Auto directional louvers
- Options include:
 - Heat pump
 - 10mm 3M™ High Air Flow filter
 - Available with unique patented NanoMist

SERIES		MF		CF	
TYPE		MONOBLOCK	MONOBLOCK	MONOBLOCK	MONOBLOCK
PRODUCTION NO		A011-10K	A011-11K	A013-10K	A013-12K
ELECTRONIC VERSION		12000E	14000E	12000E	14000E
ELECTRONIC-LCD VERSION		12000E-L	14000E-L	12000E-L	14000E-L
Cooling Capacity ¹	Btu/hr	12000	13000	12000	13000
Cooling Capacity ¹	kW	3.52	3.81	3.25	3.81
Cooling Capacity ²	Btu/hr	10000	12000	10000	12000
Cooling Capacity ²	kW	2.93	3.52	2.93	3.52
Thermostat Range	°C	18 - 32	18 - 32	18-32	18-32
Dehumidification – max	L/day	40	50	40	50
Fan Speeds		2	2	3	3
Air Flow (At High Speed)	m ³ /hr	350	380	350	420
Power Supply	V	220-240	220-240	220-240	220-240
Power Consumption	W	1110W	1340W	1150W	1380W
Current	A	5.3A	6.1A	5.1A	6.1A
Refrigerant		R410	R410	R410A	R410A
Unit Dimensions: W x D x H	mm	325 x 370 x 830	325 x 370 x 830	400 x 367 x 800	400 x 367 x 800
Carton Size: W x D x H	mm	370 x 400 x 956 or 375 x 528 x 860	370 x 400 x 956 or 375 x 528 x 860	425 x 565 x 845	425 x 565 x 845
Net Weight / Gross Weight	kg	26 / 29	27 / 29	27.5/29.5	29/31
Loading Quantity (20'/40'/40HQ)	pc	128/264/396 or 170/352/352	128/264/396 or 170/352/352	104/224/336	104/224/336