



gorenje Manual Energy label Product Fiche**DT6SY2B - GORENJE SIMPLICITY2****579205****USP :**

Sound protection

Standard sound protection

Number of speed positions

3

Number of lights

2

LED

Power saving LED lighting fixtures are highly energy-efficient, have a notably longer useful life and consume less power.

Illumination setting

On/off light switch

Number of filters

2

Washable grease filter

Metal filters in hoods, which are designed to remove fat particles, can be easily removed and cleaned. You can wash them by hand or in a dishwasher using a 'gentle wash' programme.

Filter material

Aluminium

Washable grease filter

Metal filters in hoods, which are designed to remove fat particles, can be easily removed and cleaned. You can wash them by hand or in a dishwasher using a 'gentle wash' programme.**428642**

PI Info	
Coal filter code (optional as separate purchase)	
Recirculation set number	431926
Grease filter code	419740
Odour filter	Optional
Air flow by extraction version, step 1	201 m³/h
Air flow by extraction version, step 2	410 m³/h
Maximum extraction rate by extraction operation	618 m³/h
Noise level (min.)	46 dB(A)re 1 pW
Noise level (max.)	66 dB(A)re 1 pW
Max. noise level	66 dB(A)re 1 pW
Power input/speed I	78 W
Power input/speed II	101 W
Power input/speed III	202 W

Basic information :

Product group	Kitchen hood
Decor panel options	/
Construction type	Free-standing
Brand	Gorenje
Product name / Family	Kitchen hood
Commercial code	DT6SY2B
Internal article number	579205
EAN code	3838782014543
Color body	Black
Material body	Painted steel
Color chimney	Inox
Material chimney	Stainless steel
Typology	Decorative
Installation type	Wall freestanding
Motor location	Integrated in decorative chimney
Operating mode	Convertible
Connection Rating	215 W
Current	10 A
Voltage	220-240
Frequenc	50/60
Approval certificates	CE,EAC,UA061,JUS00517,LED
Length of electrical supply cord	200 cm
Plug type	Euro
Height of the chimney (mm)	485/955
Height of product, without chimney	95 mm
Net weight	13,5 Kg
Gross weight	16,6 Kg
Width of the product	600 mm
Height of the product	95 mm
Depth of the product	435 mm

Width of the packed product	720 mm
Height of the packed product	550 mm
Depth of the packed product	460 mm
Air exhaust	Yes
Features :	
Remote control	/
Short description of the product	DT6SY2B - GORENJE SIMPLICITY2
Type of control	Mechanical
Type of manual control devices	Knob Simplicity
Number of motors	1
Total power of the motors	200 W
Number of speed settings	3
Boost position	No
Maximum output air extraction	618 m³/h
Maximum output recirculating air	572 m³/h
Illumination setting	ON/OFF
Number of lights	2
Type of lamps used	LED diode
Total power of the lamps	4.20 W
Max. noise level	66 dB(A) re 1 pW
Diameter of air outlet	150
No-return airflow flap	Yes
Grease filter material	Washable aluminium
Odour filter	No
Energy label information / Performance :	
Air flow at intensive or boost setting	/
Maximum Air flow	618 m³/h
Minimum air flow	201 m³/h
Total annual energy consumption	126,3 kWh/year
Energy efficiency class	D
Fluid Dynamic Efficiency class	D
Grease filtering efficiency class	C
Lighting efficiency	D
Noise level with boost position	/
Sound power at max. speed	66 dB
Sound power at min. speed	46 dB
Maximum extraction rate by extraction operation	618 m³/h
Energy efficiency index (2010/30/EC)	104,0 %
Fluid Dynamic Efficiency (2010/30/EC)	15,3
Grease filtering efficiency (2010/30/EC)	85,0 %
Lighting efficiency (2010/30/EC)	54,5
Noise level with boost position	/
Power consumption in standby mode (2010/30/EC)	0,0 Watt
Power consumption in off-mode - NEW (2010/30/EC)	/
Installation sketch :	

