

PRODUCT FICHE

gorenje



Hob
426159
GTW751UB

USP :

Safety function

In order to ensure maximum safety, the uninterrupted operation of each hob is time limited. When the time limit of continual operation is reached, the hob switches off automatically.

| | |
|-------------------------|----------------------------------|
| Product group | Hob |
| Wok burner | Wok triple burner |
| Ignition device | One-hand ignition device for hob |
| Wok burner | Wok triple burner |
| Type of pan support | Cast iron grid |
| High efficiency burners | ✓ |
| Protected gas burners | ✓ |

Basic information :

| | |
|---|------------------------------------|
| Product group | Hob |
| Brand | Gorenje |
| Product name / Commercial code | GTW751UB |
| Commercial code | 426159 |
| EAN code | 3838942928765 |
| Construction type | Built-in |
| Control type | Mechanical |
| Energy input | Gas |
| Total number of positions that can be used at the same time | 5 |
| Number of gas burners | 5 |
| Number of electric cooking zones | 0 |
| Number of electric plates | 0 |
| Number of radiant plates | 0 |
| Number of halogen plates | 0 |
| Number of induction plates | 0 |
| Number of electric warming zones | 0 |
| Location of control panel | Hob front |
| Gas type | G30/30 liquid gas |
| Basic external material of hob surface | Gas on tempered glass |
| Hob color | N/A |
| Hob frame material | N/A |
| Hob edges | N/A |
| Electrical connection rating | 0 W |
| Gas connection rating | 1130 W |
| Current | 0,0 A |
| Voltage | 220-240 V |
| Frequency | 50/60 Hz |
| Length of electrical supply cord | 120 cm |
| Plug type | Without plug, supply cord 3 X 0,75 |
| Width of the product | 750 mm |
| Height of the product | 111 mm |
| Depth of the product | 510 mm |
| Width of the packed product | 900 mm |
| Height of the packed product | 130 mm |
| Depth of the packed product | 590 mm |
| Min height of installation niche | 73 mm |
| Max height of installation niche | 0 mm |
| Min width of installation niche | 720 mm |
| Max width of installation niche | 0 mm |
| Depth of installation niche | 480 mm |
| Net weight | 19,0 kg |
| Gross weight | 21,0 kg |
| Location of control panel | N/A |

Features :

| | |
|----------------------------------|----------|
| Short description of the product | GTW751UB |
| Automatic programmes | No |

| | |
|----------------------------------|--------------------------------|
| Location of 1st heating element | Front left |
| Type of 1st heating element | Spare burner |
| Dimension of 1st heating element | 43 mm |
| Power of 1st heating element | 1000/0,0/0,0 W |
| Location of 2nd heating element | Rear left |
| Type of 2nd heating element | Standard burner |
| Dimension of 2nd heating element | 67 mm |
| Power of 2nd heating element | 1750/0,0/0,0 W |
| Location of 3rd heating element | Rear right |
| Type of 3rd heating element | Large burner |
| Dimension of 3rd heating element | 97 mm |
| Power of 3rd heating element | 3000/0,0/0,0 W |
| Location of 4th heating element | Front right |
| Type of 4th heating element | Standard burner |
| Dimension of 4th heating element | 67 mm |
| Power of 4th heating element | 1750/0,0/0,0 W |
| Location of 5th heating element | Centre |
| Type of 5th heating element | Triple burner |
| Dimension of 5th heating element | 134,4 mm |
| Power of 5th heating element | 3800/0,0/0,0 W |
| Power on indicator | N/A |
| Plate on indicator | / |
| Type of regulation | Stepless energy regulated |
| Type of lid | None |
| Type of pan support | Cast iron |
| Type of safety device for gas | Electromagnetic valve |
| Ignition system | Yes |
| Residual heat indicator | N/A |
| Main on/off switch | No |
| Safety device | Yes |
| Accessories included | Gas nozzles G20/20 natural gas |
| Electronic timer | No |

