## WHGC933E16X



## Freestanding wall decorative cooker hood



Polyurethane filter

TouchFree coating

LedLight

Re-circulating hoods

₩ Noise level

Useful tips

What capacity do you need?

SmartCurve

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: C

Material of housing/chimney: stainless steel and glass / stainless steel Colour of housing/chimney: glass and stainless steel / stainless steel

Lightning efficiency class: **A**Grease filtering efficiency class: **C**Fluid dynamic efficiency class: **C** 

Maximum extraction rate by extraction operation: 462 m³/h
Maximum extraction rate by recirculation operation: 392 m³/h

Venting tube diameter: 150 cm

Air flow by extraction version, step 1: 195 m³/h
Air flow by extraction version, step 2: 331 m³/h
Air flow by extraction version, step 3: 462 m³/h

Electronic control

Control setting: **Button control**Number of speed positions: **3** 

TouchFree Inox SmartCurve Lamp type: LED On/off light switch Number of lights: 2 Power of lights: 6 W

Filter material: Washable aluminium with polyurethane foam Coal filter code (optional as separate purchase): 530411

Recirculation set number: 592278

Motor type: Capacitor motor

Number of motors: 1

No return airflow flap: 150 mm

Max. noise level: 59 dB(A)re 1 pW

Height: 550 mm

Annual energy consumption: **551 kWh**Dimensions (W×H×D): **90 × 55 × 45 cm** 

Dimensions of packed product (W×H×D): 99 × 67,,50 × 51,,50 cm

Net weight: 169 kg Gross weight: 218 kg Connected load: 141 W

Nominal current of fuse: 10 amp

Product code: **560155** EAN code: **3838942121814** 

