

WHI643ORAB

gorenje
Life Simplified

Freestanding wall decorative cooker hood



P.A.S. System



AdaptTech



Timer and refresh



LedLight

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **Painted steel/glass / varnished steel**

Lightning efficiency class: **B**

Grease filtering efficiency class: **A**

Fluid dynamic efficiency class: **B**

Maximum extraction rate by extraction operation: **570 m³/h**

Venting tube diameter: **150 cm**

Air flow by extraction version, step 1: **342 m³/h**

Air flow by extraction version, step 3: **570 m³/h**

AdaptTech: Automatic fan operation

Electronic control

Control setting: **Touch control**

Timer function

Number of speed positions: **3**

Constant ventilation ReFresh

Lamp type: **LED**

Dimmer function

Number of lights: **2**

Power of lights: **8 W**

Airflow boost position (PowerBoost 2) - extraction: **740 m³/h**

Perimetric suction

Filter material: **Washable aluminium with polyurethane foam**

Grease filter indicator

Coal filter code (optional as separate purchase): **180177**

Recirculation set number: **683037**

Motor type: **Capacitor motor**

Number of motors: **1**

Number of PowerBoost functions: **2**

No return airflow flap: **150 mm**

Max. noise level: **65 dB(A)re 1 pW**

Height: **425 mm**

Min. height of the chimney: **420 mm**

Max. height of the chimney: **620 mm**

Annual energy consumption: **606 kWh**

Dimensions (W×H×D): **60 × 42,,50 × 47 cm**

Dimensions of packed product (W×H×D): **70,,50 × 52 × 56,,20 cm**

Net weight: **26 kg**

Gross weight: **30 kg**

Connected load: **284 W**

Nominal current of fuse: **10 amp**

Product code: **728153**

EAN code: **3838782027437**



<https://eg.gorenje.com/en/product/728153>