

# WHT623E5XUK

**gorenje**  
Life Simplified

## Freestanding wall decorative cooker hood



Polyurethane filter



TouchFree coating



LedLight

Re-circulating hoods



Noise level

Useful tips

What capacity do you need?

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **stainless steel / stainless steel**

Colour of housing/chimney: **stainless steel / stainless steel**

Lightning efficiency class: **A**

Grease filtering efficiency class: **B**

Fluid dynamic efficiency class: **C**

Maximum extraction rate by extraction operation: **550 m<sup>3</sup>/h**

Maximum extraction rate by recirculation operation: **413 m<sup>3</sup>/h**

Venting tube diameter: **150 cm**

Air flow by extraction version, step 1: **245 m<sup>3</sup>/h**

Air flow by extraction version, step 2: **355 m<sup>3</sup>/h**

Air flow by extraction version, step 3: **550 m<sup>3</sup>/h**

Mechanic control

Control setting: **Button control**

Number of speed positions: **3**

TouchFree Inox

Lamp type: **LED**

On/off light switch

Number of lights: **2**

Power of lights: **6 W**

Filter material: **Washable aluminium with polyurethane foam**

Coal filter code (optional as separate purchase): **698059**

Recirculation set number: **683038**

Number of motors: **1**

No return airflow flap: **150 mm**

Max. noise level: **68 dB(A)re 1 pW**

Height: **42 mm**

Min. height of the chimney: **740 mm**

Max. height of the chimney: **980 mm**

Annual energy consumption: **693 kWh**

Dimensions (W×H×D): **59,,80 × 4,,20 × 45 cm**

Dimensions of packed product (W×H×D): **71 × 59,,70 × 50,,70 cm**

Net weight: **116 kg**

Gross weight: **16 kg**

Connected load: **206 W**

Nominal current of fuse: **16 amp**

Product code: **679604**

EAN code: **3838782074318**



<https://om.gorenje.com/en/product/679604>