MAMCOR



AMCOR Dehumidifier AD120E



Features

- Up to 16.5, 18.5 and 22L/day extraction rate
- LED control soft-touch panel
- Adjustable humidistat
- 1 to 24H timer
- 2-speed fan
- 2.6L water tank capacity
- Top air grille
- Castors for easy movement
- 4-rubber feet for extreme stability (heater version)
- Easy carry handle
- Washable and odour absorbing active carbon filter
- Rotary compressor with R134A refrigerant for quiet operation
- Temperature range: 5-35°C
- Continuous drainage facility
- Options include:
- $3M^{TM}$ High Air Flow filter
- Ioniser
- PTC Heater

HOME DEHUMIDIFIERS		PLDM / DHR			PLD0			PLDK		
Electronic Version		16E	1版	22E	16E	185	216	14E	16E	185
Moisture Removal At 30 °C, 70%rh	L/day	12	16	18	12	16	18	12	16	18
Moisture Removal At 32 °C, 90%rh	L/day	16.5	18.5	22	16	18	20	16.5	18.5	22
Air Delivery At High Fan Speed	m/hr	105	120	120	105	180	180	99	113	115
Fan Speed		2	2	2	2	2	2	2	2	2
Humidistat		Y	Y	Y	Y	¥.	Y	Y	Y	Y
Water Tank Capacity	L	3	3	3	4	4	4	3	3	3
Continuous Drainage Facility		Y	Y	Y	Y	Y Y	Y	Y	Y	Y
Bectronic Touch Controls & R.h. Digital Display		Y	Y	Y	Y.	Y	Y	Y	Y	¥.
Power Supply	٧	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Power Consumption	W	220	250	360	360	360	400	235	280	390
Recommended Fuse Size		13	13	13	13	13	13	13	13	13
Refrigerant		R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A
Thermostat range	× 1	5-35	5-35	5-35	5-35	5-35	5-35	5-35	5-35	5-35
Unit Dimensions: WxDxH	mm	310 x 230 x 535			305 x 315 x 540			396 x 195 x 532		
Carton Size: W x D x H	mm	362 x 282 x 575			332 x 332 x 568			438 x 230 x 567		
Net Weight / Gross Weight	Xg	12/13	13/14	13.5/14.5	10/11	12/13	13/14	12/13	13/14	135/145
Loading quantity (201/401/401HQ)	pc	512/1056/1056			512/1056/1056			520 / 1080 / 1080		

Energy / Performance