DK63CLI



Freestanding wall chimney cooker hood





Dishwasher-safe grease filters

Knobs and handle with gold finish

Wall mounted cooker hood Venting with air extraction or recirculation Energy class: D Material of housing/chimney: varnished steel / varnished steel Colour of housing/chimney: ivory / ivory Lightning efficiency class: A Grease filtering efficiency class: E Fluid dynamic efficiency class: D Maximum extraction rate by extraction operation: 545 m3/h Maximum extraction rate by recirculation operation: 342 m3/h Venting tube diameter: 15 cm Air flow by extraction version, step 1: 355 m3/h Air flow by extraction version, step 2: 465 m3/h Air flow by extraction version, step 3: 545 m3/h Mechanic control Control setting: Button control Number of speed positions: 3 Lamp type: LED On/off light switch Number of lights: 2 Power of lights: 10 W Filter material: Aluminium Coal filter code (optional as separate purchase): 443072 Washable grease filter Motor type: Capacitor motor Number of motors: 1 No return airflow flap: 150 mm Max. noise level: 64 dB(A)re 1 pW Height: 280 mm Min. height of the chimney: 530 mm Max. height of the chimney: 860 mm Annual energy consumption: 94 kWh Dimensions (W×H×D): 60 × 28 × 50 cm Dimensions of packed product (W×H×D): 70 × 63 × 46.5 cm Net weight: 10.3 kg Gross weight: 13.1 kg Connected load: 290 W Nominal current of fuse: 10 amp Product code: 492949 EAN code: 3838942037955

