

PRODUCT FICHE

gorenje



Kitchen hood 733140 BHI611ES

USP :

Number of speed positions	3
Number of lights	2
LED	Power saving LED lighting fixtures are highly energy-efficient, have a notably longer useful life and consume less power.
Illumination setting	On/off light switch
Number of filters	1
Washable grease filter	
Filter material	Aluminium
Washable grease filter	
Coal filter code (optional as separate purchase)	416912
Odour filter	Optional
Air flow by extraction version, step 1	290 m³/h
Air flow by extraction version, step 2	340 m³/h
Maximum extraction rate by extraction operation	370 m³/h
Noise level (min.)	62 dB(A)re 1 pW
Max. noise level	67 dB(A)re 1 pW
Sound pressure / speed I	65 dB(A)re 1 pW

Basic information :

Product group	Kitchen hood
Decor panel options	N/A
Construction type	Built-in
Brand	Gorenje
Product name / Family	Kitchen hood
Commercial code	BHI611ES
Internal article number	733140
EAN code	3838782176388
Color body	Grey
Material body	Painted steel
Typology	Integrated
Installation type	Built-in into the cabinet
Motor location	Motor integrated in the hood
Operating mode	Convertible
Connection Rating	146 W
Current	N/A
Voltage	220-240 V
Frequenc	50/60 Hz
Approval certificates	CE,DEMKO
Length of electrical supply cord	150 cm
Plug type	Euro
Height of product, without chimney	208 mm
Net weight	4,8 Kg
Gross weight	5,9 Kg
Width of the product	534 mm
Height of the product	208 mm
Depth of the product	300 mm
Width of the packed product	580 mm
Height of the packed product	240 mm
Depth of the packed product	324 mm

Air exhaust

Yes

Features :

Remote control	N/A
Short description of the product	E017FII1K42BN2BSB-BHI611ES - ESSENTIAL LINE
Type of control	Mechanical
Type of manual control devices	Switches
Number of motors	1
Total power of the motors	140 W
Number of speed settings	3
Boost position	No
Maximum output air extraction	370 m ³ /h
Maximum output recirculating air	140 m ³ /h
Illumination setting	ON/OFF
Number of lights	2
Type of lamps used	LED diode
Total power of the lamps	6 W
Max. noise level	67 dB(A) re 1 pW
Diameter of air outlet	120
No-return airflow flap	No
Grease filter material	Washable aluminium
Odour filter	No

Energy label information / Performance :

Air flow at intensive or boost setting	N/A
Maximum Air flow	370 m ³ /h
Minimum air flow	290 m ³ /h
Total annual energy consumption	70,7 kWh/year
Energy efficiency class	D
Fluid Dynamic Efficiency class	E
Grease filtering efficiency class	D
Lighting efficiency	C
Noise level with boost position	N/A
Sound power at max. speed	67 dB
Sound power at min. speed	62 dB
Maximum extraction rate by extraction operation	370 m ³ /h
Energy efficiency index (2010/30/EC)	87,3 %
Fluid Dynamic Efficiency (2010/30/EC)	10,8
Grease filtering efficiency (2010/30/EC)	66,0 %
Lighting efficiency (2010/30/EC)	16,2
Noise level with boost position	N/A
Power consumption in standby mode (2010/30/EC)	N/A
Power consumption in off-mode - NEW (2010/30/EC)	N/A

