

## PRODUCT FICHE

# gorenje



## Kitchen hood 732385 WHT6SYB

### USP :

OptiStart

OptiStart - just one push of the on/off button to start the hood

TouchFree Inox

Operation indicator

Number of speed positions	3
Number of lights	2
Lamp type	LED
AdaptLight	The Gorenje Simplicity hood's innovative AdaptLight sensor feature will automatically detect when someone is standing in front of the hob to start cooking and turn on the light for you.
Number of filters	2
Filter material	Washable aluminium with polyurethane foam
Coal filter code (optional as separate purchase)	698059
Recirculation set number	683038
Grease filter code	683622
Odour filter	Optional
Air flow by extraction version, step 1	235 m³/h
Air flow by extraction version, step 2	345 m³/h
Maximum extraction rate by extraction operation	650 m³/h
Noise level (min.)	50 dB(A)re 1 pW
Max. noise level	70 dB(A)re 1 pW

### Basic information :

Product group	Kitchen hood
Decor panel options	N/A
Construction type	Free-standing
Brand	Gorenje
Product name / Family	Kitchen hood
Commercial code	WHT6SYB
Internal article number	732385
EAN code	3838782164491
Color body	N/A
Material body	Painted steel/glass
Color chimney	Black
Material chimney	Painted steel
Typology	Decorative
Installation type	Wall freestanding
Motor location	Motor integrated in the hood
Operating mode	Convertible
Connection Rating	266 W
Current	16 A
Voltage	220-240 V
Frequenc	50/60 Hz
Approval certificates	CE
Length of electrical supply cord	150 cm
Plug type	Euro
Height of the chimney (mm)	740/980
Height of product, without chimney	42 mm
Net weight	14,3 Kg

Gross weight	18,9 Kg
Width of the product	598 mm
Height of the product	42 mm
Depth of the product	456 mm
Width of the packed product	708 mm
Height of the packed product	590 mm
Depth of the packed product	491 mm
Air exhaust	Yes

### Features :

Remote control	N/A
Short description of the product	S10-WHT6SYB - GORENJE SIMPLICITY2.1
Type of control	Electronic
Type of manual control devices	Touch control
Number of motors	1
Total power of the motors	260 W
Number of speed settings	3
Boost position	No
Maximum output air extraction	650 m <sup>3</sup> /h
Maximum output recirculating air	488 m <sup>3</sup> /h
Illumination setting	N/A
Number of lights	2
Type of lamps used	LED diode
Total power of the lamps	6 W
Max. noise level	70 dB(A) re 1 pW
Diameter of air outlet	150
No-return airflow flap	Yes
Grease filter material	Washable aluminium
Odour filter	No

### Energy label information / Performance :

Air flow at intensive or boost setting	N/A
Maximum Air flow	650 m <sup>3</sup> /h
Minimum air flow	235 m <sup>3</sup> /h
Total annual energy consumption	69,7 kWh/year
Energy efficiency class	B
Fluid Dynamic Efficiency class	B
Grease filtering efficiency class	B
Lighting efficiency	A
Noise level with boost position	N/A
Sound power at max. speed	70 dB
Sound power at min. speed	50 dB
Maximum extraction rate by extraction operation	650 m <sup>3</sup> /h
Energy efficiency index (2010/30/EC)	64,5 %
Fluid Dynamic Efficiency (2010/30/EC)	25,3
Grease filtering efficiency (2010/30/EC)	86,6 %
Lighting efficiency (2010/30/EC)	38,3
Noise level with boost position	N/A
Power consumption in standby mode (2010/30/EC)	N/A
Power consumption in off-mode - NEW (2010/30/EC)	N/A

