

PRODUCT FICHE

gorenje



Kitchen hood

DK63MCLI

USP :

Perimetric suction	✓
Number of speed positions	4
Number of lights	2
LED	Power saving LED lighting fixtures are highly energy-efficient, have a notably longer useful life and consume less power.
Illumination setting	On/off light switch
Number of filters	1
Washable grease filter	Metal grease filters in Gorenje hoods are easy to remove and to clean. They can be washed manually or in a dishwasher using a delicate program.
Filter material	Aluminium
Washable grease filter	Metal grease filters in Gorenje hoods are easy to remove and to clean. They can be washed manually or in a dishwasher using a delicate program.
Coal filter code (optional as separate purchase)	180177
Grease filter code	184756
Odour filter	Optional
Air flow by extraction version, step 1	218 m³/h
Air flow by extraction version, step 2	328 m³/h
Maximum extraction rate by extraction operation	621 m³/h
Noise level (min.)	46 dB(A)re 1 pW
Max. noise level	65 dB(A)re 1 pW
Power input/speed I	88 W
Power input/speed II	106 W
Power input/speed III	140 W
Power input/speed IV	212 W

Basic information :

Product group	Kitchen hood
Decor panel options	N/A
Construction type	Free-standing
Brand	Gorenje
Product name / Family	Kitchen hood
Commercial code	DK63MCLI
Internal article number	
EAN code	3838942334689
Color body	N/A
Material body	Painted steel
Color chimney	
Material chimney	Painted steel
Typology	Decorative
Installation type	Wall freestanding
Motor location	Motor integrated in the hood
Operating mode	Convertible
Connection Rating	280 W
Current	10 A
Voltage	220-240 V
Frequenc	50 Hz
Approval certificates	CE
Length of electrical supply cord	120 cm
Plug type	Euro
Height of the chimney (mm)	590/830
Height of product, without chimney	310 mm
Net weight	15,9 Kg
Gross weight	19,52 Kg
Width of the product	600 mm
Height of the product	310 mm
Depth of the product	500 mm
Width of the packed product	710 mm

Height of the packed product	694 mm
Depth of the packed product	495 mm
Air exhaust	Yes

Features :

Remote control	
Short description of the product	
Type of control	
Type of manual control devices	
Number of motors	1
Total power of the motors	240 W
Number of speed settings	4
Boost position	No
Maximum output air extraction	621 m ³ /h
Maximum output recirculating air	545 m ³ /h
Illumination setting	ON/OFF
Number of lights	2
Type of lamps used	LED diode
Total power of the lamps	8 W
Max. noise level	65 dB(A) re 1 pW
Diameter of air outlet	150
No-return airflow flap	Yes
Grease filter material	Washable aluminium
Odour filter	No

Energy label information / Performance :

Air flow at intensive or boost setting	N/A
Maximum Air flow	621 m ³ /h
Minimum air flow	218 m ³ /h
Total annual energy consumption	117,9 kWh/year
Energy efficiency class	D
Fluid Dynamic Efficiency class	D
Grease filtering efficiency class	E
Lighting efficiency	A
Noise level with boost position	N/A
Sound power at max. speed	65 dB
Sound power at min. speed	46 dB
Maximum extraction rate by extraction operation	621 m ³ /h
Energy efficiency index (2010/30/EC)	88,6 %
Fluid Dynamic Efficiency (2010/30/EC)	13,0
Grease filtering efficiency (2010/30/EC)	61,1 %
Lighting efficiency (2010/30/EC)	48,0
Noise level with boost position	N/A
Power consumption in standby mode (2010/30/EC)	N/A
Power consumption in off-mode - NEW (2010/30/EC)	1.13

