

PRODUCT FICHE

gorenje



Combined cooker 739021 KS5250CLI

USP :

SilverMatte	✓
Door type	Double glazed oven door with one heat deflector (CompactDoor)
Door hinge	Classic door hinge
Oven type	Multisystem oven BigSpace - 70 l
Maximum oven temperature	275 °C
HomeMade Plus shape	✓
ExtraSteam	✓
FastPreheat	✓
WarmPlate	✓
Large infra heater	✓
Interior light	Illumination
PerfectGrill	✓
Product group	Cooker
Knob shape	Ergonomic knobs
Ignition device	One-hand ignition device for hob
Cast iron grid	Cast iron grid will improve the stability and enhance the appearance of the gas hob. The grid material makes it particularly durable and resistant to even the highest temperatures.
Protected gas burners	✓
Guiding of drawer	Classic
AquaClean function	✓

Basic information :

Microwave function	No
Product group	Combined cooker
Brand	GORENJE
Commercial code	KS5250CLI
Internal article number	739021
EAN code	3838782532535
Main colour of the product	BK024; Bright beige
Color / Material front	BK024; Bright beige / Painted
Construction type	Free-standing
Installation type	Free-standing
Type of control	Mechanical
Oven controls	K44A-ES - Multifunction oven with variable grill Entry steam
Cooking method	N/A
Total number of positions that can be used at the same time	4
Number of gas burners	4
Number of electric cooking zones	0
Number of electric plates	0
Number of radiant plates	0
Number of halogenous plates	0
Number of induction plates	0
Number of electric warming zones	0
Location of control panel	Cooker front
Which kind of hobs can be controlled	Gas
Energy input	Combined
Gas type	G20/20 natural gas
Gas connection rating	7800 W
Electric connection rating	3300 W
Current	N/A
Voltage	220-240 V
Frequency	50/60 Hz
Plug type	Schuko, supply cord 3 x 1.5
Adjustable feet	Yes - all
Height of the product	850 mm

Width of the product	500 mm
Depth of the product	594 mm
Height of the packed product	952 mm
Width of the packed product	576 mm
Depth of the packed product	718 mm
Min height of installation niche	0 mm
Max height of installation niche	0 mm
Min width of installation niche	0 mm
Max width of installation niche	0 mm
Depth of installation niche	0 mm
Net weight	46,1 Kg
Gross weight	49,3 Kg
Material of external sides	Steel

Features :

Electronic timer	Yes
Short description of the product	FM514C-FPD4B - KS5250CLI - IL CLAS
Control panel material	Painted
Oven guides	Wire type 1x
Grids	1
Temperature control	N/A
Time control	Mechanical
Time-setting options	Start and stop
Oven pans	2
Automatic programmes	N/A
Integrated cleaning system	Easy to clean enamel
Location of 1st heating element	Front left
Type of 1st heating element	Spare burner
Dimension of 1st heating element	54 mm
Power of 1st heating element	1000/0,0/0,0 W
Location of 2nd heating element	Rear left
Type of 2nd heating element	Standard burner
Dimension of 2nd heating element	74 mm
Power of 2nd heating element	1900/0,0/0,0 W
Location of 3rd heating element	Rear right
Type of 3rd heating element	Standard burner
Dimension of 3rd heating element	77 mm
Power of 3rd heating element	1900/0,0/0,0 W
Location of 4th heating element	Front right
Type of 4th heating element	Large burner
Dimension of 4th heating element	99 mm
Power of 4th heating element	3000/0,0/0,0 W
Power ON indicator	No
Plate ON indicator	/
Type of lid	Steel
Type of pan support	Cast iron
Type of safety device for gas	Electromagnetic valve
Ignition system	Yes
Residual heat indicator	Without
Main on/off switch	No
Safety device	
Timer	Electronic programing timer with analog display
Control panel information	Pictograms and text
Cavity material	N/A
Oven lighting	Yes
Position of interior lights	Rear
Grill motor with rotisserie set	No
Meat probe	No
Storage compartment	Pull-out drawer
Additional equipment included	Deep baking pan - 1 Baking tray EM - 1 Gas nozzles G30/30 liquid gas Oven grid - 1

Energy label information / Performance :

Energy efficiency class - NEW (2010/30/EC)	A
The power consumption in off-mode	0,5 W
Energy consumption per cycle conventional (2010/30/ES)	1,03
Energy consumption gas oven per cycle conventional (2010/30/ES)	0,0
Energy consumption per cycle forced air convection (2010/30/ES)	0,8
Usable volume of cavity (2010/30/ES)	70
Number of cavities - NEW (2010/30/EC)	1
Energy consumption forced air convection	0,0
Energy efficiency index (2010/30/EC)	95,2
Energy consumption conventional (kWh)	1,03 kWh
Energy consumption forced air convection (kWh)	0,8 kWh
Noise	46 db(A) re 1pW
Product size	Large

